



Annex B2 - Product environmental attributes Computers and computer monitors

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Acer	Logo
Company name *	Acer Inc	
Contact information *	Name: RU Jan	acer
e-mail address	e-mail: RU.Jan@acer.com	
Internet site *	www.acer.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	Notebook			
Commercial name *	C936, C936T			
Model number *	N23Q19			
Issue date *	2023-09-26			
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other			
Additional information				

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products.

Model number *	N23Q19	Logo	
Issue date *	2022-09-26		acer

Product 6	environmental attributes - Legal requirements	Require	ment met		
Item		Yes	No n.a.		
P1	Hazardous substances and preparations				
P1.1*	Products do comply with current European RoHS Directive. (See legal reference and NOTE B1)	\boxtimes			
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.	\boxtimes			
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.				
P1.4*	Products do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated terphenyl (PCT) in preparations (see legal reference).				
P1.5*	Products do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).				
P1.6*	Parts with direct and prolonged skin contact do not release nickel in concentrations above $0.5 \mu g/cm^2/week$ (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:2011-5.				
P1.7*	REACH Article 33 information about substances in articles is available at (add URL or mail contact): https://www.acer-group.com/sustainability/en/chemical-management-plans.html				
P2	Batteries				
P2.1*	If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal symbol. Information on proper disposal is provided in user manual. (See legal reference)				
P2.2*	Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal reference)				
P2.3*	Batteries and accumulators are readily removable. (See legal reference)	\boxtimes			
P2.4*	Documentation includes the number of cycles the (secondary) battery can withstand. (See legal reference)	\boxtimes			
P2.5*	When internal batteries of a notebook computer cannot be "accessed and replaced by a nonprofessional user", the related text is present and legible on the external packaging (see legal reference)				
P3	Conformity verification & Eco design (ErP)				
P3.1*	The product is CE-marked to show conformance with applicable legal requirements (see legal reference). The Declaration of Conformity can be requested at (add link or e-mail address):				
P3.2*	The product complies with the applicable Eco design requirements for energy-related products, (see legal reference).				
	Required information is; given in item P15 or added to this document,	\boxtimes			
P5	available at (add URL): www.acer.com				
P5.1*	Product packaging Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium and				
	hexavalent chromium by weight of these together.				
P5.2*	The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s used (see legal reference).	, 🔼			
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal Protocol (see legal reference).				
	Comment: Legal reference has no maximum concentration values.				
P6	Treatment information				
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).	\boxtimes			

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number *	N23Q19	Logo	2606
Issue date *	2022-09-26		acer

Product	environmental attributes - Market requirements (See General NOTE GN below) - Environmental conscious design	Require	mont	met
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.			n.a.
P7	Design	Yes	No	ii.a.
	Disassembly, recycling			
P7.1*	Parts that have to be treated separately are easily separable	\boxtimes		
P7.2*	Plastic materials in covers/housing have no surface coating.		\boxtimes	
P7.3*	Plastic parts > 100 g consist of one material or of easily separable materials.	\boxtimes		
P7.4*	Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.	\boxtimes		
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.	\boxtimes		
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	\boxtimes		
	Product lifetime			
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives		\boxtimes	
P7.8*	Upgrading can be done using commonly available tools	\boxtimes		
P7.9	Spare parts are available after end of production for: years			
P7.10	Service is available after end of production for: years			
	Material and substance requirements			
P7.11*	Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: PC+ABS Material type: Material type: Material type:			
P7.12	Insulation materials of external electrical cables are PVC free.		X	
P7.13	Insulation materials of internal electrical cables are PVC free.			
P7.14	External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content.) <u>\</u>		
P7.15	Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See ⁵ NOTE B2)			
P7.16	Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: >PC+ABS-TD15FR(40)< & >PC+ABS-FR(40)< & >PC+ABS-TD15(REC60)FR(40)<			
P7.17	Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: 9,10-Dihydro-9-oxa-10-phosphaphenanthrene 10-Oxide, CAS #: 35948-25-5			
	<u>Alt. 2:</u> Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4:			
P7.18	Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: Aromatic polyphosphate, CAS #: 181028-79-5 (See NOTE B4) 2. Chemical name: , CAS #: "			
	3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40)			
P7.19	Plastic parts > 25 g, are free from flame retardant substances/ preparations above 0,1% are classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See NOTE B3)			

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm.

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

Model number *	N23Q19	Logo	
Issue date *	2022-09-26		acer

Material and substance requirements (continued) P7.20' Postconsumer recycled plastic material content is used in the product (See NOTE B6):	Product	Product environmental attributes - Market requirements (continued)					Requi	reme	nt met
P7.20* Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 17.8063%. P7.21* Biobased plastic material content is used in the product (See NOTE B7): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic parts' weight) is %. Or b) The weight of the biobased plastic material is 0. P7.22* Light sources are free from mercury, i.e. less than 0,1 mg/lamp. If mercury is used specify: Number of lamps: and maximum mercury content per lamp: mg P7.23* If product includes an integral display, the total mercury content in the integrated display: mg P8. Batteries P8.1* Battery chemical composition: Lithium Battery P9. Energy consumption (See NOTE B8) P9.1 For the product the following power levels or energy consumptions are reported: Energy mode * Power level at 100 V AC P15 V AC Power level at 230 V AC Reference/Standard for energy modes and test method * ENERGY STAR V8.0 (External power supply / charger plugged in the wall outlet but disconnected from the product.) PTEC * 1.41W 1.42W 1.51W ENERGY STAR V8.0 ENERGY STAR V8.0 DEFECTORS * 1.41W 1.42W 1.51W ENERGY STAR V8.0 ENERGY STAR V8.0 DEFECTORS * 1.41W 1.42W 1.51W ENERGY STAR V8.0 DISplay resolution *: 1920*1080megapixels Default time to enter energy save mode: 10 minutes		,							
If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 17.863%. P7.21* Biobased plastic material content is used in the product (See NOTE B7): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic by weight) is 9. P7.22* Light sources are free from mercury, i.e. less than 0,1 mg/lamp. If mercury is used specify. Number of lamps: and maximum mercury content per lamp: mg P7.23* If product includes an integral display, the total mercury content in the integrated display: mg P8. Batteries P8.1* Battery chemical composition: Lithium Battery P9 Energy consumption (See NOTE B8) P9.1 For the product the following power levels or energy consumptions are reported: Energy mode * Power level at 100 V AC 115 V AC 230 V AC modes and test method EPS No-load (External power supply / charge plugged in the wall outlet but disconnected from the product.) P1.41W 1.42W 1.51W ENERGY STAR V8.0 ETEC * 1.41W 1.42W 1.51W ENERGY STAR V8.0 Display resolution *: 1920*1080megapixels Default time to enter energy save mode: 10 minutes Default time to enter energy save mode: 10 minutes		Material and subs	tance requirements	(continued)					
a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 17.8063%. P7.21* Biobased plastic material is 107 g. If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic by weight) is %. Of the weight of the biobased plastic material is g. P7.22* Light sources are free from mercury, i.e. less than 0.1 mg/lamp. If mercury is used specify. Number of lamps: and maximum mercury content per lamp: mg P7.23* If product includes an integral display, the total splay is and maximum mercury content per lamp: mg P8 Batteries P9 Energy consumption (See NOTE B8) P9.1 For the product the following power levels or energy consumptions are reported: Energy mode * Power level at 115 V AC Power level at 230 V AC modes and test method * EPS No-load (External power supply / charge) plugged in the wall outlet but disconnected from the product.) ETEC * I.41W 1.42W 1.51W ENERGY STAR V8.0 ETEC * Typical Energy Consumption * ETEC * J.41W 1.42W 1.51W ENERGY STAR V8.0 ETEC * J.41W 1.42W 1.51W ENERGY STAR V8.0 Display resolution *: 1920*1080megapixels Default time to enter energy save mode: 10 minutes Default time to enter energy save mode: 10 minutes Default time to enter energy save function is provided with the product.	P7.20*	Postconsumer recy	cled plastic material	content is used in the	product (See NOTE B6):			
percentage of total plastic by weight) is 17.8063%. P7.21* Biobased plastic material is 107 g. P7.21* Biobased plastic material content is used in the product (See NOTE B7): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic parts' weight) is %. P7.22* Light sources are free from mercury, i.e. less than 0,1 mg/lamp. If mercury is used specify: Number of lamps: and maximum mercury content per lamp: mg P7.23* If product includes an integral display, the total mercury content in the integrated display: mg P8. Batteries P8. 11* Battery consumption (See NOTE B8) P9. 1 For the product the following power levels or energy consumptions are reported: Energy mode * Power level at 100 V AC 115 V AC 230 V AC 804 Mercury modes and test method * EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.) PTEC * 0.03W 0.03W 0.03W 0.07W ENERGY STAR V8.0 ETEC * 1.41W 1.42W 1.51W ENERGY STAR V8.0 ETEC * 1.41W 1.42W 1.51W ENERGY STAR V8.0 ETEC * 1.41W 1.42W 1.51W ENERGY STAR V8.0 Display resolution *: 1920*1080*megapixels External Power Supply Efficiency Level (International Efficiency Marking Protocol) *: V/ Display resolution *: 1920*1080*megapixels Default time to enter energy save mode: 10 minutes Default time to enter energy save function is provided with the product.									
P7.21* Biobased plastic material content is used in the product (See NOTE B7):									
P7.21* Biobased plastic material content is used in the product (See NOTE B7): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic by weight) is %. or b) The weight of the biobased plastic material is g. P7.22* Light sources are free from mercury, i.e. less than 0,1 mg/lamp. If mercury is used specify: Number of lamps: and maximum mercury content per lamp: mg P7.23* If product includes an integral display, the total mercury content in the integrated display: mg P8.1* Batteries P8.1* Battery chemical composition: Lithium Battery P9 Energy consumption (See NOTE B8) P9.1 For the product the following power levels or energy consumptions are reported: Energy mode * Power level at 115 V AC 230 V AC Reference/Standard for energy modes and test method * EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.) PTEC * 1.41W 1.42W 1.51W ENERGY STAR V8.0 ETEC * Annual Energy Consumption 1.41W 1.42W 1.51W ENERGY STAR V8.0 EXternal Power Supply Efficiency Level (International Efficiency Marking Protocol) *: VI Display resolution *: 1920*1080megapixels Default time to enter energy save mode: 10 minutes P9.2* Information about the energy save function is provided with the product.		or	, , ,	,					
If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic by weight) is %. or b) The weight of the biobased plastic material is g. P7.22* Light sources are free from mercury, i.e. less than 0,1 mg/lamp. If mercury is used specify: Number of lamps: and maximum mercury content per lamp: mg mg mg mercury is used specify: Number of lamps: and maximum mercury content per lamp: mg	P7 21*	Richased plastic m	aterial content is use	d in the product (See I	NOTE B7):			\square	
a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic by weight) is %. P7.22* Light sources are free from mercury, i.e. less than 0,1 mg/lamp. If mercury is used specify. Number of lamps: and maximum mercury content per lamp: mg P7.23* If product includes an integral display, the total mercury content in the integrated display: mg P8. Batteries P9.1 Battery chemical composition: Lithium Battery P9 Energy consumption (See NOTE B8) P9.1 For the product the following power levels or energy consumptions are reported: Energy mode* Power level at 100 V AC 115 V AC 230 V AC modes and test method modes and test method modes and test method modes and test method modes and test method. EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.) PTEC* 1.4fW 1.42W 1.5fW ENERGY STAR V8.0 ETEC* 2.1.4fW 1.42W 1.5fW ENERGY STAR V8.0 ETEC* 1.2.3skWh/year 12.47kWh/year 13.27kWh/year ENERGY STAR V8.0 EXTERNAL Power Supply Efficiency Level (International Efficiency Marking Protocol)*: V/ Display resolution*: 1920*1080*megapixels Default time to enter energy save mode: 10 minutes P9.2* Information about the energy save function is provided with the product.	17.21	biobased plastic III	aterial content is use	a in the product (See i	NOTE BIJ.		Ш		
of total plastic by weight) is %. Or b) The weight of the biobased plastic material is g. P7.22* Light sources are free from mercury, i.e. less than 0,1 mg/lamp. If mercury is used specify: Number of lamps: and maximum mercury content per lamp: mg P7.23* If product includes an integral display, the total mercury content in the integrated display: mg									
P7.22* Light sources are free from mercury, i.e. less than 0,1 mg/lamp. If mercury is used specify: Number of lamps: and maximum mercury content per lamp: mg P7.23* If product includes an integral display, the total mercury content in the integrated display: mg					: material content (calc	ulated as a percentage			
P7.22* Light sources are free from mercury, i.e. less than 0,1 mg/lamp. mg mg mg mg mg mg mg m		•	by weight) is	/ 0.					
If mercury is used specify: Number of lamps: and maximum mercury content per lamp: mg P7.23* If product includes an integral display, the total mercury content in the integrated display: mg			the biobased plastic	material is g.					
P7.23* If product includes an integral display, the total mercury content in the integrated display: mg P8 Batteries P8.1* Battery chemical composition: Lithium Battery P9.1 For the product the following power levels or energy consumptions are reported: Energy mode * Power level at 100 V AC Power level at 115 V AC Power level at 230 V AC Power supply / charger plugged in the wall outlet but disconnected from the product.) PTEC * Typical Energy Consumption PTEC * Typical Ener	P7.22*						\boxtimes		
P8 Batteries P8.1* Battery chemical composition: Lithium Battery P9 Energy consumption (See NOTE B8) P9.1 For the product the following power levels or energy consumptions are reported: Energy mode * Power level at 100 V AC Power level at 115 V AC Power level at 230 V AC Power level at 115 V AC Power level at 115 V AC Power level at 230 V AC Power level at 115 V	D7.00*			mps: and maxir	num mercury content p	er lamp: mg			
P8.1* Battery chemical composition: Lithium Battery P9		•	an integral display, tr	ne total mercury conte	nt in the integrated disp	lay: mg			
P9 Energy consumption (See NOTE B8) P9.1 For the product the following power levels or energy consumptions are reported: Energy mode * Power level at 100 V AC 115 V AC 230									
P9.1 For the product the following power levels or energy consumptions are reported: Energy mode * Power level at 100 V AC Power level at 115 V AC Power level at 1230 V AC Reference/Standard for energy modes and test method * EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.) PTEC * Typical Energy Consumption PTEC * Typical Energy STAR V8.0 PTEC * Typical Energy STAR				Battery					
Energy mode * Power level at 100 V AC Power level at 115 V AC Power level at 230 V AC Reference/Standard for energy modes and test method * Power level at 230 V AC Reference/Standard for energy modes and test method * Power level at 115 V AC Power level at 230 V AC Reference/Standard for energy modes and test method * Power level at 120 V AC Power level at 120 V AC Reference/Standard for energy modes and test method * Power level at 120 V AC Power level at 120 V AC Reference/Standard for energy modes and test method * Power level at 120 V AC Power leve									
100 V AC 115 V AC 230 V AC modes and test method *	P9.1	For the product the	following power leve	els or energy consump	tions are reported:				
(External power supply / charger plugged in the wall outlet but disconnected from the product.) PTEC * Typical Energy Consumption 1.41W 1.42W 1.51W ENERGY STAR V8.0 ETEC * Annual Energy Consumption 12.33kWh/year 12.47kWh/year 13.27kWh/year ENERGY STAR V8.0 EXTERMALL Power Supply Efficiency Level (International Efficiency Marking Protocol) *: VI Display resolution *: 1920*1080 megapixels Default time to enter energy save mode: 10 minutes P9.2* Information about the energy save function is provided with the product.	Energy mo	ode *						ЭУ	
charger plugged in the wall outlet but disconnected from the product.) PTEC * Typical Energy Consumption 1.41W 1.42W 1.51W ENERGY STAR V8.0 ETEC * Annual Energy Consumption 12.33kWh/year Annual Energy Consumption External Power Supply Efficiency Level (International Efficiency Marking Protocol) *: VI Display resolution *: 1920*1080 megapixels Default time to enter energy save mode: 10 minutes P9.2* Information about the energy save function is provided with the product.	EPS No-lo	ad	0.03W	0.03W	0.07W	ENERGY STAR V8.0)		
outlet but disconnected from the product.) PTEC * Typical Energy Consumption 1.41W 1.42W 1.51W ENERGY STAR V8.0 ETEC * Annual Energy Consumption 12.33kWh/year Annual Energy Consumption External Power Supply Efficiency Level (International Efficiency Marking Protocol) *: VI Display resolution *: 1920*1080 megapixels Default time to enter energy save mode: 10 minutes P9.2* Information about the energy save function is provided with the product.									
the product.) PTEC * Typical Energy Consumption 1.41W 1.42W 1.51W ENERGY STAR V8.0 ETEC * Annual Energy Consumption 12.33kWh/year Annual Energy Consumption External Power Supply Efficiency Level (International Efficiency Marking Protocol) *: VI Display resolution *: 1920*1080 megapixels Default time to enter energy save mode: 10 minutes P9.2* Information about the energy save function is provided with the product.									
PTEC * Typical Energy Consumption 1.41W 1.42W 1.51W ENERGY STAR V8.0 ETEC * Annual Energy Consumption 12.33kWh/year Annual Energy Consumption 12.47kWh/year 13.27kWh/year ENERGY STAR V8.0 External Power Supply Efficiency Level (International Efficiency Marking Protocol) *: V/ Display resolution *: 1920*1080 megapixels Default time to enter energy save mode: 10 minutes P9.2* Information about the energy save function is provided with the product.									
Typical Energy Consumption ETEC * Annual Energy Consumption 12.33kWh/year	-	,	1 44\\\\	4.42\\\\	4.54\\\\	ENERGY STAR VO	•		
ETEC * Annual Energy Consumption		eray Consumption	1.4100	1.4200	1.5100	ENERGY STAR VO.	,		Ш
Annual Energy Consumption External Power Supply Efficiency Level (International Efficiency Marking Protocol) *: VI Display resolution *: 1920*1080*megapixels Default time to enter energy save mode: 10 minutes P9.2* Information about the energy save function is provided with the product.	. , p	orgy comoumpaion							
Annual Energy Consumption External Power Supply Efficiency Level (International Efficiency Marking Protocol) *: VI Display resolution *: 1920*1080*megapixels Default time to enter energy save mode: 10 minutes P9.2* Information about the energy save function is provided with the product.	ETEC *		12.33kWh/year	12.47kWh/year	13.27kWh/year	ENERGY STAR V8.0)		
Display resolution *: 1920*1080megapixels Default time to enter energy save mode: 10 minutes P9.2* Information about the energy save function is provided with the product.	Annual En								
Display resolution *: 1920*1080megapixels Default time to enter energy save mode: 10 minutes P9.2* Information about the energy save function is provided with the product.									
Default time to enter energy save mode: 10 minutes P9.2* Information about the energy save function is provided with the product.	External Power Supply Efficiency Level (International Efficiency Marking Protocol) *: VI								
P9.2* Information about the energy save function is provided with the product.	Display resolution * : 1920*1080 megapixels								
	Default time to enter energy save mode: 10 minutes								
P9.3 Energy efficiency class (monitors only):	P9.2* Information about the energy save function is provided with the product.								
	P9.3	P9.3 Energy efficiency class (monitors only):							\boxtimes

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available;

see http://www.ecma-international.org/publications/standards/Ecma-370.htm.

Model number *	N23Q19	Logo	
Issue date *	2022-09-26		acer

Product	environmental	attributes - Market requirements (con	ntinued)		Require	men	met
Item			•		Yes	No	n.a.
P10	Emissions						
	Noise emission	n – Declared according to ISO 9296 (See NO					
P10.1	Mode	Mode description	Statistical upper $L_{WA,c}$ (B)	er limit A-weighted sound po	wer level,		
	Idle	* Idle	* 2.7				\Box
	Operation	*	*				X
	Other mode						
	Measured accor	rding to: SISO 7779 ECMA-74 Other (only if not covered	d by ECMA-74)				
	Electromagneti		,				
P10.4	Computer displa program(s):	ay meets the requirement for low frequency el	lectromagnetic fields	of the following voluntary			
P12	Ergonomics for	r computing products					
P12.1*	The display mee	ets the ergonomic requirements of ISO 9241-	307 for visual displa	y technologies.			\boxtimes
P12.2*	The physical inp	out device meets the requirements of ISO 999	95 and ISO 9241-410).		\boxtimes	
P13	Packaging and	documentation					
P13.1*							
P13.2*		primary packaging is free from PVC.	,		\boxtimes		
P13.3*	For product primary corrugated fiberboard packaging, specify the contained percentage of minimum post-consumer recovered fiber content: 92 & 100 %						
P13.4*	Specify media for user and product documentation (tick box):						
P13.5		mplete this item if paper documentation used) ct documentation on paper media is chlorine- pecify:					
	Totally chlorine-						
	Elemental chlori						
	Processed chlor	rine-free			\boxtimes		
P14	Voluntary prog	ırams					
P14.1		ets the requirements of the following voluntar	y program(s):				
	ENERGY STAR Eco-label: Eco-label:	Criteria version: 8.0 Criteria version: Criteria version:	Date: 2023/08/28 Date: Date:	Product category: <i>Notebo</i> Product category: Product category:	ok,1		
D4E	Additional infa	rmetion (See NOTE B40)					
P15 P10	Additional information (See NOTE B10)						
P7.15	Noise Emission: Declared A-weighted sound pressure level LpAm (Idle 24.3 dB) Printed circuit boards, PCBs (without components) are low halogen: The low halogen of power adapter is optional.						
77.10	r mileu circuit	boards, r obs (without components) are it	ow naiogen. The lo	w narogen or power duapt	er is opui	oriai.	

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm.

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive)* * Specific exemptions apply for certain products and applications.	P1.1, P3.1
Regulation (EC) 1907/2006 (REACH Regulation), annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2006/66/EC (Battery and accumulators Directive), as amended.* * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2014/35/EU (Low Voltage Directive)	P3.1
Directive 2014/30/EU (EMC Directive)	P3.1
Directive 2014/53/EU (RE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Commission Regulation (EC) No 278/2009 of 6 April 2009 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for no-load condition electric power demand and average active efficiency of external power supplies	P3.1, P3.2, P9.1
COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers	P2.4, P2.5, P3.1, P3.2, P7.23, P9.1
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1
Implementing Regulation (EU) 2019/290 establishing the format for registration and reporting of producers of electrical and electronic equipment to the register.	
Commission Implementing Regulation 2017/699 establishing a common methodology for the calculation of the weight of electrical and electronic equipment (EEE) placed on the national market in each Member State and a common methodology for the calculation of the quantity of waste electrical and electronic equipment (WEEE) generated by weight in each Member State.	